

# SALICE HINGE QUICK REFERENCE TO COMMON OVERLAY APPLICATIONS

## Overlay: Frameless Cabinet: Using 4mm (5/32") TAB Distance (K)

What is TAB (K) Distance?	Hinge Overlay Choices				★ Indicates preferred choice
	Full Overlay Hinge	1/2" Overlay Hinge	Half (3/8") Overlay Hinge	Inset Hinge	
Mounting Plate Thickness Choices ↓	"A"	"D"	"G"	"P"	Desired Overlay
0mm	3/4" Overlay 19mm	9/16" Overlay 14mm	★ 3/8" Overlay 10mm		
2mm	11/16" Overlay 17mm	1/2" Overlay 12.5mm	★ 5/16" Overlay 4mm	Inset Door Plus Adjustment	
3mm	5/8" Overlay 16mm	7/16" Overlay 11mm	★ 9/32" Overlay 7mm (Plus Adjustment)	★ Inset Door	
6mm	★ 1/2" Overlay 12.5mm	5/16" Overlay 8mm	5/32" Overlay 4mm		
9mm	3/8" Overlay 10mm	3/16" Overlay 5mm (Plus Adjustment)	Inset Door Plus Adjustment		
12mm	1/4" Overlay 6mm	3/32" Overlay 2mm (Plus Adjustment)	Inset Door		
18mm	Inset Door Plus Adjustment				

## Overlay: Face Frame Cabinet, Euro Hinge & Mounting Plate: Using 4mm (5/32") TAB Distance (K)

1" = 25.4mm Mounting Plate Thickness Choices ↓	Hinge Overlay Choices				★ Indicates preferred choice
	Full Overlay Hinge	1/2" Overlay Hinge	Half (3/8") Overlay Hinge	Inset Hinge	
"A"	"D"	"G"	"P"	Desired Overlay	
1mm	3/4" Overlay 19mm	1/2" Overlay 12.5mm	★ 3/8" Overlay 10mm		
4mm	9/16" Overlay 15mm	3/8" Overlay 10mm	1/4" Overlay 6mm		
BAL3R59		Inset Door (Use 3mm Tab)	★ Inset Door		
BAM3R09	1 1/4" Overlay 32mm (Use 6mm Tab (K))				

## Remaining Steps To Complete Hinge & Mounting Plate Selection

1. Select the angle of opening of the hinge.    94 Degree <input type="checkbox"/> 110 Degree <input type="checkbox"/> 120 Degree <input type="checkbox"/> 155 degree <input type="checkbox"/> 165 Degree <input type="checkbox"/>	Adjustment Range
2. Select the fixing method to attach the hinge to the door.    Screw-on <input type="checkbox"/> Press-in dowel <input type="checkbox"/> Rapido <input type="checkbox"/> Logica <input type="checkbox"/>	
3. Select hinge closing style.    Self closing <input type="checkbox"/> Soft Closing "Silentia" <input type="checkbox"/> Self Opening "Push" <input type="checkbox"/> Free swinging <input type="checkbox"/>	
4. Select mounting plate grade:    Premium (2 cam adjustment) <input type="checkbox"/> Economy (1 cam adjustment) <input type="checkbox"/>	
5. Select fixing method to attach the mounting plate to the cabinet.    Wood screw <input type="checkbox"/> Euro screw <input type="checkbox"/> Expanding dowel <input type="checkbox"/>	
6. For "Silentia" hinges: Verify cup boring depth with customer:    Series 100 = <b>12.5mm</b> <input type="checkbox"/> Series 200 = <b>15.5mm</b> <input type="checkbox"/> Series 700 = <b>13.5mm</b> <input type="checkbox"/>	
7. For "Push" hinges: Select a release device style:    Mechanical release device <input type="checkbox"/> Magnetic release device <input type="checkbox"/>	

### Finding The Mounting Plate Thickness In The Part Number

BAR3R09 = 0mm thick	BAR3R39 = 3mm thick	BAR3R99 = 9mm thick	BAV3EV9F = 18mm thick	BAU3R49 = 4mm thick
BAR3R29 = 2mm thick	BAR3R69 = 6mm thick	BAR3RC9 = 12mm thick	BAU3R19 = 1mm thick	BAL3R59 = 5mm thick

Technical assistance

800.222.9652