

REQUIREMENTS

INTRODUCTION

This bulletin summarizes the fundamental quality standards that are required when fabricating and installing DuPont™ Corian® solid surface products.

OVERVIEW

Proper fabrication and installation of DuPont™ Corian® solid surface is essential. This bulletin addresses the minimum requirements. For further information on the requirements please review the relevant *DuPont™ Corian® Solid Surface Fabrication/Installation Fundamentals* bulletin.

Some products have unique characteristics that impact fabrication techniques. The specialized techniques are addressed in *DuPont™ Corian® Solid Surface Product Fabrication* bulletins.

Commercial applications often have specialized requirements. These are addressed in *DuPont™ Corian® Solid Surface Specialty Application* bulletins, which supersede the information provided in this document.

A. HARD SEAMING DUPONT™ CORIAN® SOLID SURFACE

1. Reinforce all seams using a full length Corian® solid surface seam reinforcement strip attached with DuPont™ Joint Adhesive. This reinforcement strip also serves as the seam support.
2. Use only DuPont™ Joint Adhesive for rigid seams.

B. CUTOUTS IN DUPONT™ CORIAN® SOLID SURFACE

1. Only use routers for cutouts. Use a minimum $\frac{3}{8}$ " (10 mm) or larger diameter bits. Round over top and bottom edges of the cutout to a $\frac{1}{16}$ " (1.5 mm) minimum radius.
2. Remove all cutting imperfections, e.g. nicks, tool marks, etc., to create a smooth surface. Final step should be 100 µ/P150 grade or finer.
3. Smooth out the back edge of horizontal tops behind cook-tops by sanding. Round over top and bottom edges to $\frac{1}{16}$ " (1.5 mm) radius.
4. Provide full cutout perimeter support within 3" (76 mm) from the edge of cutouts. The cutout support must be attached to the main support structure. For oval lavatories the support may be rectangular, with the distance measured from the closest points of the lavatory to the support. Supports for sinks and lavatories should leave at least an $\frac{1}{8}$ " (3 mm) gap between the support and the bowl flange. Supports for heat-generating appliances in residential applications should be no closer than 1" (25 mm) from the cutout.
5. High-strength cutouts are required for all residential heat-generating appliances.
6. For heat-generating appliances in residential applications apply 3M™ Aluminum Foil Tape 425 or 427 (DuPont stock code D11920096) around the perimeter of the cutouts. The tape should be applied so that it extends $\frac{1}{4}$ " (6 mm) below the top and across the top surface so that entire flange of the heat-generating appliance rests on the tape.

Commercial hot-cold horizontal applications require specialized fabrication and installation techniques. Contact an Authorized Distributor of DuPont™ Corian® Solid Surface for guidelines.

REQUIREMENTS

C. DUPONT™ CORIAN® SOLID SURFACE INSTALLATIONS

C.1. Support

1. Full perimeter support is required. Addition cross-span support may also be required. This support must satisfy the “zero load” test requirement. When a 300 pound (136 kg) weight is placed at the center-point of the support structure the span must deflect less than $\frac{1}{8}$ " (3 mm) over 10' (3 m). Permanently installed and heavy equipment will require dedicated support.
2. Horizontal support must be in plane and true to within $\frac{1}{8}$ " (3 mm) over 10' (3 m).
3. Use only dabs of flexible silicone adhesive no less than 12" (305 mm) apart to fasten Corian® solid surface to the support structure.
4. Support overhangs exceeding 6" (152 mm) for $\frac{1}{2}$ " (12 mm) Corian® sheet and 12" (305 mm) for $\frac{3}{4}$ " (19 mm) Corian® sheet.
5. For residential applications:
 - Provide perimeter support (top edges of cabinets, framing, etc.). Islands may require cross spans if they are not already present as part of the cabinetry.
 - Do not install Corian® solid surface over underlayment or over old countertops. Integral “dust covers” may be left in place if removal is unacceptable to the customer.

C.2. Clearances

1. Allow $\frac{1}{16}$ " (1.5 mm) minimum clearance between installations and any surface that could constrain expansion and contraction of the installation.
2. In wet wall installations, leave a $\frac{1}{2}$ " (13 mm) air gap at the bottom of the substrate wall to prevent water leaks from wicking up between the Corian® solid surface and the substrate.

C.3. Attachments

1. Corian® solid surface should not be rigidly adhered to other solid surface products. Use only silicone to adhere Corian® solid surface to any material other than itself. There is one approved exception; Corian® bowls may be mounted on Zodiaq® quartz surfaces using DuPont™ Joint Adhesive.
2. Never install mechanical fasteners (screws, nails, etc.) into Corian® solid surface. Brass and plastic inserts designed for solid surfaces are the only generally approved mechanical fasteners. Specialty applications may have other allowable fasteners. The design must accommodate thermal expansion in the structure to which the Corian® solid surface is fastened as the inserts will not accommodate any movement.

C.4. Inside Corners

1. All inside corners of L, U, etc., shaped installations require a minimum $\frac{1}{2}$ " (13 mm) radius to reduce corner stresses. V-grooved inside corner edges will require a 1" (25 mm) minimum radius.
2. Place seams in Corian® edge buildup strips a minimum of 1" (25 mm) past the end of the inside corner radius.

This information is based on technical data that E.I. du Pont de Nemours and Company and its affiliates ("DuPont") believe to be reliable, and is intended for use by persons having technical skill and at their own discretion and risk. DuPont cannot and does not warrant that this information is absolutely current or accurate, although every effort is made to ensure that it is kept as current and accurate as possible. Because conditions of use are outside DuPont's control, DuPont makes no representations or warranties, express or implied, with respect to the information, or any part thereof, including any warranties of title, non-infringement of copyright or patent rights of others, merchantability, or fitness or suitability for any purpose and assumes no liability or responsibility for the accuracy, completeness, or usefulness of any information. This information should not be relied upon to create specifications, designs, or installation guidelines. The persons responsible for the use and handling of the product are responsible for ensuring the design, fabrication, or installation methods and process present no health or safety hazards. Do not attempt to perform specification, design, fabrication, or installation work without proper training or without the proper personal protection equipment. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents. DuPont shall have no liability for the use of or results obtained from such information, whether or not based on DuPont's negligence. DuPont shall not be liable for (i) any damages, including claims relating to the specification, design, fabrication, installation, or combination of this product with any other product(s), and (ii) special, direct, indirect or consequential damages. DuPont reserves the right to make changes to this information and to this disclaimer. DuPont encourages you to review this information and this disclaimer periodically for any updates or changes. Your continued access or use of this information shall be deemed your acceptance of this disclaimer and any changes and the reasonableness of these standards for notice of changes.

© E.I. du Pont de Nemours and Company 2012. All rights reserved.

The DuPont Oval, DuPont™, The miracles of science™, and Corian® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company ("DuPont") or its affiliates. 3M is a trademark of 3M Company. K-25705 7/12